

FTA5102E2

High-performance 2 FXS

VoIP Adapter

FTA5102E2 is a high-performance VoIP adapter with 2 FXS ports. It can not only provide 2 SIP lines for users to make calls but also support T.38 and T.30 fax protocols.

FTA5102E2 supports dual LAN network ports and NAT routing function. As a portable VoIP adapter, it can be used as an internal desktop switch. Users can enjoy convenient data connection and HD voice.



Key Features and Benefits

2 FXS Ports

FXS port can connect analog phones, fax machines, POS machines and other devices to the VoIP system, and it supports T.38 and T.30 protocols to provide broad compatibility for the access of fax machines.

2 LAN Ports

With 2 LAN ports to provide data transmission for PC, printer, IPTV.

LED Indicators

The LED indicators include power indicator, WAN port indicator, LAN port indicator and FXS port indicator.

Stand-alone Device

FTA5102E2 is a stand-alone device, which requires no PC to make clear and reliable Internet calls.

TR069 & SNMP Protocols

Equipped with advanced management protocols such as SNMP and TR069, which is easy to achieve unified deployment and centralized management.

Broad Compatibility

FTA5102E2 is based on SIP V2.0 and compatible with most service providers, which brings great convenience when deploying VoIP network.

Power

- > AC/DC adapter
- > AC Input: 100~240V, 50~60Hz
- > DC Output: 12V, 1A

Operating System

- > Linux 2.6.36

I/O Interfaces

- > 1 x RJ-45 for 10/100Mbps WAN port
- > 2 x RJ-45 for 10/100Mbps LAN port
- > 2 x RJ11 FXS port
- > RST

Environmental

- > Operation temperature: 0~50°C
- > Storage temperature: -20~ 85°C
- > Relative humidity: 10%~90% Non-condensing

Audio Codec

- > G.711(A/u), PESQ > 4
- > G.729A/AB, PESQ > 3.6
- > T.30 FAX with G.711
- > Real time FAX over IP via T.38
- > Adaptive jitter buffer
- > Voice activity detection
- > Comfort noise generation
- > Echo cancellation

Management

- > Upgradeable firmware
- > HTTP/HTTPS Web management
- > IVR management
- > Local and remote syslog protocol
- > Auto provisioning
- > SNTP time synchronization
- > Multi-user level access
- > SNMPv2
- > TR069
- > Telnet
- > FACS

Protocols

- > SIP V2.0 (RFC3261, RFC3262, RFC3263, RFC3264, RFC3265, RFC3515, RFC3891, RFC3892, 3GPP, IMS)
- > SDP (RFC2327)
- > RTP/RTCP (RFC1889/RFC1890)
- > NAPTR for SIP URI lookup (RFC2915)
- > STUN (RFC2030)
- > ARP/RARP (RFC826/RFC903)
- > SNTP (RFC2030)
- > DHCP/PPPoE/Static
- > PPTP/L2TP VPN
- > HTTP/HTTPS Server for Web Management
- > DNS/DNS SRV (RFC1706/RFC2782)
- > TFTP/HTTP/HTTPS for Auto Provisioning
- > DHCP option for SIP server (RFC3361)
- > TR069 (TR098, TR104)
- > IEEE802.1Q VLAN/802.1p/DSCP
- > Support IPv4 and IPv6

FAX Support

- > T.38 fax with G711 fallback
- > T.38 Fax supports Error Correction Mode (ECM)
- > T.38 Fax, maximum speed of 14.4kbps

FXS Features

- > 3-way conference
- > Music on hold
- > DTMF mode: In-band, RFC2833, SIP INFO
- > Call hold
- > Call forwarding
- > Call mute
- > Call transfer
- > Call waiting
- > Speed dial
- > Caller ID and CWCID
- > Hotline
- > Dial plan
- > Black list
- > Call log
- > Multicast: PA system, Announcement, paging system

Applications


- > NAT and bridge
- > MAC address cloning
- > DHCP client and DHCP server
- > VPN (PPTP, L2TP)
- > SIP proxy redundancy
- > NAT Traversal (STUN)
- > DMZ
- > Layer 3 QoS
- > IP conflict detection
- > SNTP

Dimension and Weight

- > Dimension: 120mm (L) x 80mm (W) x 32mm (H)
- > Weight: 119g (N.W)

Package

- > Package content:
 - FTA5102E2
 - Ethernet cable
 - Quick installation guide
 - Power adapter
- > Qty/CTN: 10 PCS
- > N.W/CTN: 4.45 kg
- > G.W/CTN: 4.3 kg
- > Giftbox size: 200mm x 150mm x 60mm
- > Carton meas.: 340mm x 330mm x 230mm



About Flyingvoice

Flyingvoice is a leading manufacturer of VoIP phones, VoIP adapters and VoIP routers, which are widely used throughout the world and highly praised by international carriers, ITSP, ISP and company users.

Driven by ongoing innovation of VoWLAN, Flyingvoice is committed to making easier VoIP products by enabling the enterprise network and united communication. Our people are continuously improving our products and expanding product applications tailored to clients' requirements, which make you collaborate securely, effectively and efficiently – anytime & anywhere.

Copyright

Copyright © Flyingvoice Network Technology Co., Ltd. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Flyingvoice Network Technology Co., Ltd.

Technical Support

Visit www.flyingvoice.com for product documents and FAQ, or contact Flyingvoice by email at support@flyingvoice.com. We'll get you the help you need.



Flyingvoice Network Technology Co., Ltd.

Website: www.flyingvoice.com

Add: 1801-1802, Building 1, Chongwen Park, Nanshan Zhiyuan,
Nanshan District, Shenzhen, Guangdong, 518000 China

Copyright © 2022 Flyingvoice Network Technology Co., Ltd. All Rights